


ANTIKA

DESCRIPTION: Paver **TEXTURE:** Smooth

Pallet Overview*





Smooth **Chocolate Brown**

Smooth **Chestnut Brown**

Smooth **Shale Grey**


Smooth **Onyx Black**

Specifications per pallet

	Imperial	Metric
A  Product dimension (L × W × H) A	Variable × 2 ⅜	Variable × 60
B  Product dimension (L × W × H) B	Variable × 2 ⅜	Variable × 60
C  Product dimension (L × W × H) C	Variable × 2 ⅜	Variable × 60
D  Product dimension (L × W × H) D	Variable × 2 ⅜	Variable × 60
E  Product dimension (L × W × H) E	Variable × 2 ⅜	Variable × 60
F  Product dimension (L × W × H) F	Variable × 2 ⅜	Variable × 60
G  Product dimension (L × W × H) G	Variable × 2 ⅜	Variable × 60
Cubing	87 ft²	8.10 m²
Approx. Weight	2 183 lbs	990 kg
Number of rows	9	
Coverage per row	9.67 ft²	0.90m²

Laying Patterns Options

01 | Random



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

NOTES

The Antika paver is perfect as a filler in a circle, around a fan design or on a winding pathway. Antika can also be used as a mosaic frame around any design.

See page 6 for icons description.

See page 19 for more information about applications.

See page 56 to 58 for more technical information. When used in a permeable pavement application, see page 93 to 97 for more technical information.

JOINT WIDTH: variable
% OF SURFACE OPENING: variable
INFILTRATION RATE: 993 in./hr (25 227 mm/hr)

*Pallet layout may vary.